



Technical Data Sheet

<p>General:</p> <p>Article number: 536xxx</p> <p>Description: Colad Nitrile Gloves Black</p>																
<p>Specification:</p> <p>Material: Nitrile Size: 285mm. Thickness: 6 mil.</p> <p>Features: Flexible Powder Free Silicon Free Latex Free Single Use</p> <p>CE Mark: CE 0321</p> <p>Available in:</p> <table border="1" data-bbox="178 1299 962 1478"> <thead> <tr> <th>Size</th> <th>Dispenserbox 60 pcs.</th> <th>Dispenserbox 400 pcs.</th> </tr> </thead> <tbody> <tr> <td>M</td> <td>Art.no. 536000</td> <td>Art.no. 536400</td> </tr> <tr> <td>L</td> <td>Art.no. 536002</td> <td>Art.no. 536402</td> </tr> <tr> <td>XL</td> <td>Art.no. 536004</td> <td>Art.no. 536404</td> </tr> <tr> <td>2XL</td> <td>Art.no. 536006</td> <td>Not available</td> </tr> </tbody> </table>		Size	Dispenserbox 60 pcs.	Dispenserbox 400 pcs.	M	Art.no. 536000	Art.no. 536400	L	Art.no. 536002	Art.no. 536402	XL	Art.no. 536004	Art.no. 536404	2XL	Art.no. 536006	Not available
Size	Dispenserbox 60 pcs.	Dispenserbox 400 pcs.														
M	Art.no. 536000	Art.no. 536400														
L	Art.no. 536002	Art.no. 536402														
XL	Art.no. 536004	Art.no. 536404														
2XL	Art.no. 536006	Not available														
<p>Remarks:</p> <ul style="list-style-type: none"> - Strong, flexible and high tensile strength. - Long sleeves (285mm.) and textured surface for better grip. - Powder, Silicon and Latex Free to prevent skin irritation. - Especially suitable for working with paints and solvents. <div data-bbox="279 1780 726 1881" style="text-align: center;">  </div> <p>Personal Protective Equipment (PPE) CAT III according to European directive 89/686/EEC. PPE of complex design protects against risks that cause irreversible damage to health.</p>																

EC Type examination test results:

Tested in accordance with EN374-2:2003	Performance level	AQL	Inspection levels
 Specified: Level 2 (AQL<1.5) acc. to producer	Level 3	< 0.65	G1
	Level 2	< 1.5	G1
	Level 1	< 4.0	S4

Tested acc. to EN374-3	N-heptane 99% - Level 3 Sodium Hydroxide 40% - Level 6	
	Level 1: > 10 minutes	Level 4: > 120 minutes
	Level 2: > 30 minutes	Level 5: > 240 minutes
	Level 3: > 60 minutes	Level 6: > 480 minutes



Tested acc. to EN 1149-3, Method 2:
Induction decay time.

Test according to EN 388

Abrasion: 0 Cut: 0 Tear: 0 Perforation: 0



Notified body number: 0321

Approved by:



SATRA Technology Centre
Northamptonshire, NN16 8SD
United Kingdom

Created by:

EMM International BV
Bohemenstraat 19, 8028 SB Zwolle, The Netherlands
www.emm.com



T +31(0)38 467 66 00
www.colad.co