

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: HALLEY UV200

Other means of identification:

UFI: RTX1-70Y3-6002-5AHA

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Bicomponent base. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

Roberlo S.A.U.

1.3

Ctra. Nacional II, Km. 706,5

17457 Riudellots de la Selva - Gerona - España

Details of the supplier of the safety data sheet:

Phone: +34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (España) (GMT +1:00) - Fax: +34972477394

msds@roberlo.com

1.4 Emergency telephone number: +44 (0)1924 431679 / 112 / +34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO

(Spain) (GMT + 1:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Eye Dam. 1: Serious eye damage, Category 1, H318 Flam. Liq. 2: Flammable liquids, Category 2, H225 Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger









Hazard statements:

H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

Contains Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate, Hexamethylene diacrylate.

Substances that contribute to the classification

Oxybis(methyl-2,1-ethanediyl) diacrylate; Pentaerythritol tetrakis(3-mercaptopropionate); 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide

UFI: RTX1-70Y3-6002-5AHA

Date of compilation: 19/07/2022 Version: 1 Page 1/17

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins in solvents

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	67-64-1	acetone(1)	ATP CLP00	
	200-662-2 606-001-00-8 01-2119471330-49- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	10 - <25 %
CAS:	13048-33-4	Hexamethylene diac	rylate ⁽¹⁾ Self-classified	
	235-921-9 607-109-00-8 01-2119484737-22- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	5 - <10 %
CAS:	57472-68-1	Oxybis(methyl-2,1-e	thanediyl) diacrylate ⁽¹⁾ Self-classified	
	260-754-3 Non-applicable 01-2119484629-21- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	5 - <10 %
CAS:	7575-23-7	Pentaerythritol tetra	kis(3-mercaptopropionate)(1) Self-classified	
	231-472-8 Non-applicable 01-2119486981-23- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1A: H317 - Warning	5 - <10 %
CAS: EC:	1187441-10-6 810-703-1	2-Propenoic acid, 2-phosphorus oxide ⁽¹⁾	methyl-, 2-hydroxyethyl ester, reaction products with Self-classified	
	Non-applicable 01-2120140608-57- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Skin Sens. 1B: H317 - Danger	2,5 - <5 %
CAS:	84434-11-7	Ethyl phenyl(2,4,6-ti	rimethylbenzoyl)phosphinate(1) Self-classified	
	282-810-6 Non-applicable 01-2119987994-10- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Sens. 1B: H317 - Warning	2,5 - <5 %
CAS:	141-78-6	Ethyl acetate(2)	ATP CLP00	
	205-500-4 607-022-00-5 01-2119475103-46- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	0,5 - <1 %
CAS:	108-65-6 203-603-9	2-methoxy-1-methy	lethyl acetate ⁽²⁾ Self-classified	
	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	0,1 - <0,3 %
CAS: 123-31-9		1,4-dihydroxybenzer	ne ⁽¹⁾ ATP ATP01	
	204-617-8 604-005-00-4 01-2119524016-51- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Carc. 2: H351; Eye Dam. 1: H318; Muta. 2: H341; Skin Sens. 1: H317 - Danger	0,01 - <0,1 %
CAS:	110-82-7	cyclohexane(2)	ATP CLP00	
	203-806-2 601-017-00-1 01-2119463273-41- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	<0,01 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 (2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Date of compilation: 19/07/2022 Version: 1 Page 2/17

roberlo

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		M-factor
Pentaerythritol tetrakis(3	B-mercaptopropionate)	Acute	10
CAS: 7575-23-7	EC: 231-472-8	Chronic	10
1,4-dihydroxybenzene		Acute	10
CAS: 123-31-9	EC: 204-617-8	Chronic	1

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

roberlo°

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

(10) 2019/1031.						
Identification	Oc	ccupational exposure limits				
acetone	IOELV (8h)	500 ppm	1210 mg/m ³			
CAS: 67-64-1	IOELV (STEL)					
Ethyl acetate	IOELV (8h)	200 ppm	734 mg/m ³			
CAS: 141-78-6 EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³			
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³			
CAS: 108-65-6	IOELV (STEL)	100 ppm	550 mg/m ³			
cyclohexane	IOELV (8h)	200 ppm	700 mg/m ³			
CAS: 110-82-7 EC: 203-806-2	IOELV (STEL)					

DNEL (Workers):

	Short exposure		Long exposure		
Identification		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable
Hexamethylene diacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 13048-33-4	Dermal	Non-applicable	Non-applicable	2,77 mg/kg	Non-applicable
EC: 235-921-9	Inhalation	Non-applicable	Non-applicable	24,5 mg/m ³	Non-applicable
Oxybis(methyl-2,1-ethanediyl) diacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 57472-68-1	Dermal	Non-applicable	Non-applicable	2,77 mg/kg	Non-applicable
EC: 260-754-3	Inhalation	Non-applicable	Non-applicable	24,48 mg/m ³	Non-applicable
Pentaerythritol tetrakis(3-mercaptopropionate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7575-23-7	Dermal	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
EC: 231-472-8	Inhalation	Non-applicable	40,13 mg/m ³	1,74 mg/m ³	40,13 mg/m ³
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1187441-10-6	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
EC: 810-703-1	Inhalation	Non-applicable	Non-applicable	7,05 mg/m ³	Non-applicable
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 84434-11-7	Dermal	Non-applicable	Non-applicable	1,4 mg/kg	Non-applicable
EC: 282-810-6	Inhalation	Non-applicable	Non-applicable	4,93 mg/m ³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
1,4-dihydroxybenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-31-9	Dermal	Non-applicable	Non-applicable	3,33 mg/kg	Non-applicable
EC: 204-617-8	Inhalation	Non-applicable	Non-applicable	2,1 mg/m ³	Non-applicable
cyclohexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	2016 mg/kg	Non-applicable
EC: 203-806-2	Inhalation	1400 mg/m ³	1400 mg/m ³	700 mg/m ³	700 mg/m ³

DNEL (General population):

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable

Date of compilation: 19/07/2022 Version: 1 Page 5/17



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation











SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short 6	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Hexamethylene diacrylate	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
CAS: 13048-33-4	Dermal	Non-applicable	Non-applicable	1,66 mg/kg	Non-applicable
EC: 235-921-9	Inhalation	Non-applicable	Non-applicable	7,2 mg/m ³	Non-applicable
Oxybis(methyl-2,1-ethanediyl) diacrylate	Oral	Non-applicable	Non-applicable	2,08 mg/kg	Non-applicable
CAS: 57472-68-1	Dermal	Non-applicable	Non-applicable	1,66 mg/kg	Non-applicable
EC: 260-754-3	Inhalation	Non-applicable	Non-applicable	7,24 mg/m ³	Non-applicable
Pentaerythritol tetrakis(3-mercaptopropionate)	Oral	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
CAS: 7575-23-7	Dermal	Non-applicable	Non-applicable	2,5 mg/kg	Non-applicable
EC: 231-472-8	Inhalation	Non-applicable	20,07 mg/m ³	0,43 mg/m ³	20,07 mg/m ³
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
CAS: 1187441-10-6	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
EC: 810-703-1	Inhalation	Non-applicable	Non-applicable	3,53 mg/m ³	Non-applicable
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
CAS: 84434-11-7	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
EC: 282-810-6	Inhalation	Non-applicable	Non-applicable	0,87 mg/m ³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
1,4-dihydroxybenzene	Oral	Non-applicable	Non-applicable	0,6 mg/kg	Non-applicable
CAS: 123-31-9	Dermal	Non-applicable	Non-applicable	1,66 mg/kg	Non-applicable
EC: 204-617-8	Inhalation	Non-applicable	Non-applicable	1,05 mg/m³	Non-applicable
cyclohexane	Oral	Non-applicable	Non-applicable	59,4 mg/kg	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	1186 mg/kg	Non-applicable
EC: 203-806-2	Inhalation	412 mg/m ³	412 mg/m ³	206 mg/m ³	206 mg/m ³

PNEC:

Identification				
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Hexamethylene diacrylate	STP	2,7 mg/L	Fresh water	0,007 mg/L
CAS: 13048-33-4	Soil	0,094 mg/kg	Marine water	0,001 mg/L
EC: 235-921-9	Intermittent	Non-applicable	Sediment (Fresh water)	0,493 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,049 mg/kg
Oxybis(methyl-2,1-ethanediyl) diacrylate	STP	100 mg/L	Fresh water	0,003 mg/L
CAS: 57472-68-1	Soil	0,001 mg/kg	Marine water	0 mg/L
EC: 260-754-3	Intermittent	0,034 mg/L	Sediment (Fresh water)	0,009 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Pentaerythritol tetrakis(3-mercaptopropionate)	STP	2,39 mg/L	Fresh water	0,00003 mg/L
CAS: 7575-23-7	Soil	0,000184 mg/kg	Marine water	0,0000034 mg/L
EC: 231-472-8	Intermittent	0,00034 mg/L	Sediment (Fresh water)	0,00102 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,000102 mg/kg
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	STP	0,4 mg/L	Fresh water	0,165 mg/L
CAS: 1187441-10-6	Soil	0,46 mg/kg	Marine water	0,017 mg/L
EC: 810-703-1	Intermittent	1,65 mg/L	Sediment (Fresh water)	2,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,28 mg/kg

Date of compilation: 19/07/2022 Version: 1 Page 6/17

roberlo°

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	STP	Non-applicable	Fresh water	0,00101 mg/L
CAS: 84434-11-7	Soil	0,0475 mg/kg	Marine water	0,000101 mg/L
EC: 282-810-6	Intermittent	0,0101 mg/L	Sediment (Fresh water)	0,24 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,024 mg/kg
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
1,4-dihydroxybenzene	STP	0,71 mg/L	Fresh water	0,00057 mg/L
CAS: 123-31-9	Soil	0,00064 mg/kg	Marine water	0,000057 mg/L
EC: 204-617-8	Intermittent	0,00134 mg/L	Sediment (Fresh water)	0,0049 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00049 mg/kg
cyclohexane	STP	3,24 mg/L	Fresh water	0,207 mg/L
CAS: 110-82-7	Soil	3,38 mg/kg	Marine water	0,207 mg/L
EC: 203-806-2	Intermittent	0,207 mg/L	Sediment (Fresh water)	16,68 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,68 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	- ∰	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 13,4 % weight

180,92 kg/m³ (180,92 g/L) V.O.C. density at 20 °C:

Average carbon number: 3,09

Average molecular weight: 60,44 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 181,14 kg/m³ (181,14 g/L)

EU limit for the product (Cat. B.C): 540 g/L (2010) Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid Appearance: Fluid Colour: Grey Odour: Characteristic Odour threshold: Non-applicable *

Volatility:

56 - 4200 °C Boiling point at atmospheric pressure: Vapour pressure at 20 °C: 17732 Pa

Vapour pressure at 50 °C: 59062,5 Pa (59,06 kPa) Non-applicable *

Evaporation rate at 20 °C:

Product description:

Density at 20 °C: 1350 kg/m3

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

roberlo

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Relative density at 20 °C: 1,35

Dynamic viscosity at 20 °C: 153 cP

Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: >20,5 mm²/s Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Immiscible Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: -17 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 240 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Non-applicable *

Corrosive to metals:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

roberlo

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	A	cute toxicity	Genus
Oxybis(methyl-2,1-ethanediyl) diacrylate	LD50 oral	>2000 mg/kg	
CAS: 57472-68-1	LD50 dermal	>2000 mg/kg	
EC: 260-754-3	LC50 inhalation	>20 mg/L	
Hexamethylene diacrylate	LD50 oral	>5000 mg/kg	Rat
CAS: 13048-33-4	LD50 dermal	3600 mg/kg	Rabbit
EC: 235-921-9	LC50 inhalation	>20 mg/L	
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	LD50 oral	>2000 mg/kg	
CAS: 1187441-10-6	LD50 dermal	>2000 mg/kg	
EC: 810-703-1	LC50 inhalation	>20 mg/L	
Pentaerythritol tetrakis(3-mercaptopropionate)	LD50 oral	1000 mg/kg	Rat
CAS: 7575-23-7	LD50 dermal	>2000 mg/kg	
EC: 231-472-8	LC50 inhalation	>20 mg/L	
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	LD50 oral	>5000 mg/kg	Rat
CAS: 84434-11-7	LD50 dermal	2000 mg/kg	Rat
EC: 282-810-6	LC50 inhalation	>20 mg/L	
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	>20 mg/L	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	>5000 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
l,4-dihydroxybenzene	LD50 oral	450 mg/kg	Rat
CAS: 123-31-9	LD50 dermal	>2000 mg/kg	
EC: 204-617-8	LC50 inhalation	>5 mg/L	
cyclohexane	LD50 oral	5100 mg/kg	Rat
CAS: 110-82-7	LD50 dermal	>2000 mg/kg	
EC: 203-806-2	LC50 inhalation	>20 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Hexamethylene diacrylate	LC50	0,38 mg/L (96 h)	Oryzias latipes	Fish
CAS: 13048-33-4	EC50	2,7 mg/L (48 h)	Daphnia magna	Crustacean
EC: 235-921-9	EC50	2,33 mg/L (72 h)	N/A	Algae

Date of compilation: 19/07/2022 Version: 1 Page 11/17



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
Pentaerythritol tetrakis(3-mercaptopropionate)	LC50	0,034 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 7575-23-7	EC50	0,35 mg/L (48 h)	Daphnia magna	Crustacean
EC: 231-472-8	EC50	0,12 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	LC50	1,89 mg/L (96 h)	Danio rerio	Fish
CAS: 84434-11-7	EC50	2,26 mg/L (48 h)	Daphnia magna	Crustacean
EC: 282-810-6	EC50	1,01 mg/L (72 h)	Desmodesmus subspicatus	Algae
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
1,4-dihydroxybenzene	LC50	0,638 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 123-31-9	EC50	0,134 mg/L (48 h)	Daphnia magna	Crustacean
EC: 204-617-8	EC50	0,33 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
cyclohexane	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 110-82-7	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 203-806-2	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean
Hexamethylene diacrylate	NOEC	0,072 mg/L	Oryzias latipes	Fish
CAS: 13048-33-4 EC: 235-921-9	NOEC	0,14 mg/L	Daphnia magna	Crustacean
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	De	egradability	Biode	egradability
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %
Hexamethylene diacrylate	BOD5	Non-applicable	Concentration	32 mg/L
CAS: 13048-33-4	COD	Non-applicable	Period	28 days
EC: 235-921-9	BOD5/COD	Non-applicable	% Biodegradable	65 %
Pentaerythritol tetrakis(3-mercaptopropionate)	BOD5	Non-applicable	Concentration	10 mg/L
CAS: 7575-23-7	COD	Non-applicable	Period	28 days
EC: 231-472-8	BOD5/COD	Non-applicable	% Biodegradable	26 %
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 84434-11-7	COD	Non-applicable	Period	28 days
EC: 282-810-6	BOD5/COD	Non-applicable	% Biodegradable	5 %
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
1,4-dihydroxybenzene	BOD5	Non-applicable	Concentration	600 mg/L
CAS: 123-31-9	COD	Non-applicable	Period	28 days
EC: 204-617-8	BOD5/COD	Non-applicable	% Biodegradable	80 %

Date of compilation: 19/07/2022 Version: 1 Page 12/17



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradab	ility
cyclohexane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 110-82-7	COD	Non-applicable	Period	28 days
EC: 203-806-2	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioac	cumulation potential
acetone	BCF	1
CAS: 67-64-1	Pow Log	-0.24
EC: 200-662-2	Potential	Low
Pentaerythritol tetrakis(3-mercaptopropionate)	BCF	24
CAS: 7575-23-7	Pow Log	3.03
EC: 231-472-8	Potential	Low
Ethyl acetate	BCF	30
CAS: 141-78-6	Pow Log	0.73
EC: 205-500-4	Potential	Moderate
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
1,4-dihydroxybenzene	BCF	3
CAS: 123-31-9	Pow Log	0.59
EC: 204-617-8	Potential	Low
cyclohexane	BCF	66
CAS: 110-82-7	Pow Log	3.44
EC: 203-806-2	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorp	otion/desorption		Volatility
acetone	Кос	1	Henry	2,93 Pa·m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Hexamethylene diacrylate	Koc	126	Henry	5E-2 Pa·m³/mol
CAS: 13048-33-4	Conclusion	Moderate	Dry soil	No
EC: 235-921-9	Surface tension	Non-applicable	Moist soil	No
Pentaerythritol tetrakis(3-mercaptopropionate)	Koc	264	Henry	Non-applicable
CAS: 7575-23-7	Conclusion	Moderate	Dry soil	Non-applicable
EC: 231-472-8	Surface tension	Non-applicable	Moist soil	Non-applicable
Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate	Koc	2344.2	Henry	Non-applicable
CAS: 84434-11-7	Conclusion	Low	Dry soil	Non-applicable
EC: 282-810-6	Surface tension	Non-applicable	Moist soil	Non-applicable
Ethyl acetate	Кос	59	Henry	13,58 Pa·m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
1,4-dihydroxybenzene	Koc	50	Henry	0E+0 Pa·m³/mol
CAS: 123-31-9	Conclusion	Very High	Dry soil	Non-applicable
EC: 204-617-8	Surface tension	6,35E-3 N/m (360,18 °C)	Moist soil	Non-applicable
cyclohexane	Koc	Non-applicable	Henry	Non-applicable
CAS: 110-82-7	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-806-2	Surface tension	2,465E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

roberlo°

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 12: ECOLOGICAL INFORMATION (continued)

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:





14.1UN number or ID number:UN126314.2UN proper shipping name:PAINT14.3Transport hazard class(es):3Labels:3

14.4 Packing group: II
14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 163, 367, 640D, 650

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1263
 14.2 UN proper shipping name: PAINT
 14.3 Transport hazard class(es): 3
 Labels: 3

14.4 Packing group: II14.5 Marine pollutant: Yes

14.6 Special precautions for user

Special regulations: 367, 163

EmS Codes: F-E, S-E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable **14.7 Maritime transport in bulk** Non-applicable

according to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 UN number or ID number: UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
Labels: 3

14.4 Packing group: II
14.5 Environmental hazards: Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Maritime transport in bulk** Non-applicable

according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- —tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 2: H351 - Suspected of causing cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Muta. 2: H341 - Suspected of causing genetic defects.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: ${\sf H317}$ - ${\sf May}$ cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method Eye Dam. 1: Calculation method Skin Sens. 1A: Calculation method Aquatic Acute 1: Calculation method Aquatic Chronic 1: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

Safety data sheet This SDS is an English translation of COMMISSION R



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

HALLEY UV200









SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.